ANEST IWATA

AIRLESS EQUIPMENT

www.anest-iwataeu.com

ALG 7 WB TE
Manual Spray Gun

stainless steel

FOR WATER BASED PAINTS

- Nozzle Gland Set Thread UNF 11/16”
- Trigger load: 2,26 kgf.
- High safety design: the resisting pressure is quadruple to the maximum working pressure.
- Easy maintenance: it is not necessary to use any special tools to disassemble/assemble. The needle valve set is a complete assembly.
- Inner material of swivel joint in Stainless Steel SUS303

CE Ex II 2 G X
declaration of ATEX conformity for use in zone 1 and in zone 2

Model	bar	Use	Filter	Hose connection	Operating temperature	Noise level	g
ALG-7 TE	250 bar	general	100 mesh	G 1/4”	5-40° C	62.9 dB (A)	440
ALG-72		general	100 mesh	G 1/4”			415
ALG-73		high viscosity	--	G 3/8”			450

ALG-7 TE and ALG 73 Four fingers operation trigger
ALG-72 Two fingers operation trigger

ANEST IWATA

ANEST IWATA Europe s.r.l.
C.so Vigevano, 46
10155 Torino - Italy
Tel. +39 011 22 74 438
Fax +39 011 22 74 406
info@anest-iwataeu.com
www.anest-iwataeu.com

Distributed by: